


Τελευταία ανανέωση υλικού:

Σύντομη περιγραφή:

T.:

W.:



INNVESTIO

Business Unit:



XEIKON PANTHER 2.0 SERIES

Durability? High-gloss?
Clear-on-clear? Go Panther!



As truly direct and dedicated digital printing technology specialists, we believe you should deal with your challenges in your very own way. That is why we offer a wider range of digital technologies for a wide range of label applications.

The Xeikon Panther family combines our trademark quality, versatility and speed with the possibilities of UV inkjet. It's Panther technology. It makes quality versatile. It's very Xeikon. You'll be ready for whatever is behind the next turn.

specifications

A division of **FlintGroup**

XEIKON PANTHER 2.0 SERIES specifications

YOU'LL BE READY FOR WHATEVER IS BEHIND THE NEXT TURN. ESPECIALLY FOR:

- Durable labels (industrial, chemicals,...); our patented DuraCure technology reaches the highest durability
- Health & Beauty products: high gloss, "Squeezable" products. UV inks are perfect. Makes the product keep "standing out".
- Premium drinks & beers: clear-on-clear labels in high quality perfectly possible with our robust substrate handling technology.



XEIKON MANUFACTURING N.V.

T. +32 443 13 11


Duwijckstraat 17 - 2500 Lier

www.xeikon.com - info@xeikon.com

XP2.0S_EU_SEP2021_spec

© 2021 Xeikon International NV. All rights reserved. All trademarks are property of their respective owners. No parts of this brochure may be reproduced, copied, adapted, translated or transmitted in any form or by any means, without prior written permission from Xeikon. The material in this brochure is for informational purposes only and is subject to change without prior notice. No responsibility or liability is assumed by Xeikon for any errors, which may appear in this brochure.

	XEIKON PX2200	XEIKON PX3300	XEIKON PX3300 HC	XEIKON PX30000
Print process	Piezo DoD UV inkjet DuraCure technology (LED- and mercury cured)			Piezo DoD UV inkjet mercury cured
Color configuration	4 printstations (CMYK) 5 printstations (CMYK + White)			6 printstations: CMYK + Orange + Violet 8 printstations: CMYK + Orange + Violet + Double White
Addressability and grey levels	600 x 600 dpi with 4 grey levels			
Media width	150-350 mm		200-350 mm	200-340 mm
maximum imaging width	220 mm wide	330 mm wide		333 mm wide
Max. printing speed	50 m/min			70 m/min
Press throughput	660 sqm/hr	990 sqm/hr		1428 sqm/hr
Inks	PantherCure Ink			PantherCure XT-D inks (High durability) PantherCure XT-E UV inks (Reduced migration)
Ink supply	Exterior indication of empty Ink tank			
Print media	Self adhesive media: coated paper, vinyl, PP, PE, PET, metalised, clear-on-clear			
Unwinder	Integrated		External	Integrated
Maximum unwinder / rewinder reel diameter	650 mm		1320 mm	1000 mm
Media weight	60-350 gsm		60-300 gsm (max roll weight 800 kg)	60-350 gsm
Media thickness	90-350 µ			
Workflow	Xeikon X-800 digital front end			
Embedded media control	webcleaner, corona treater, splice table, anti-static bar, active webaligner, splice detection, print media cooling roll			
features	pre-printed stock sensor (optional) digital microscope			pre-printed stock sensor (standard) web reverse mode XTflow, XTclean, XTstitch
Printer dimensions (LxWxH)	4.160 x 2.220 x 1.900 mm		6.860 x 2.220 x 1.900 mm	5.614 x 1.925 x 1.735 mm
Environment requirements	temperature range 20-25 °C optimal humidity range 40-60%, dust controlled environment preferred			optimal temperature range 20-22 °C optimal humidity range 40-60%, dust controlled environment preferred
Weight	3.100 kg		3.930 kg	3.100 kg



INNVESTIO

INNVESTIO

Θέση Πάτημα, ΒΙ.ΠΕ. Καλυβίων
Καλύβια Θορικού, 190 10 (Τ.Θ. 101)

T.: 210 220 6100, 22990 61000

E.: hello@innvestio.gr

W.: www.innvestio.gr - www.innvestio.bg

